

Since 1898
CONSEW®

Models

206RBL-18 / 206RBL-25 / 206RBL-30-1




LONG-ARM, HEAVY DUTY, SINGLE NEEDLE, LOCKSTITCH MACHINES

WITH
CENTRALIZED ARM LUBRICATION
RESERVOIR-OILED HOOK WITH MICROMETRIC CONTROL VALVE
LARGE HORIZONTAL AXIS ROTARY HOOK AND BOBBIN
ADJUSTABLE REVERSE FEED
LOCKING STITCH REGULATOR
SAFETY CLUTCH *Note: The 206RBL-30-1 does NOT have a Safety Clutch*
FACTORY BUILT SOLID MOLDED CASTING

LARGE
BOBBIN

AS SEEN ON
TV
AND USED BY

West Coast
CUSTOMERS
West Coast Customs



Special features for the 206RBL30-1

- Oil Pump System with Pump, Oil Pan and Adjustable Oil Flow
- Adjustable Oil Gauge
- Engageable Center Handwheel

18", 25" and 30" LONG-ARM VERSIONS
HEAVY DUTY, SINGLE NEEDLE
TRIPLE FEED: *DROP FEED, NEEDLE FEED
AND ALTERNATING (WALKING) PRESSER FEET*
LOCKSTITCH MACHINE

206RBL-18 / 206RBL-25 / 206RBL-30-1



APPLICATIONS

- For sewing light to heavy-weight materials such as leather, vinyl, upholstery, synthetics, canvas and various coated and laminated products.
- Designed for stitching such products as auto, boat and furniture upholstery, tarpaulins, covers, sails, tents, camping trailer covers, awnings, umbrellas, tops, bags, luggage, handbags, travelware accessories, sports and camping equipment, wearing apparel, outdoor clothing, canvas shoes, slippers, orthopedic appliances etc.

FEATURES

- Extra long stitch - 2 1/2 S.P.I. (10mm)
- Large Bobbin. Bobbin can be changed without removing object being sewn
- Thread release finger (for heavy thread)
- Reverse Stitching
- Centralized arm lubrication. Reservoir-oiled hook with micrometric control valve.
- Adjustable reverse stitching can be same length as forward stitch.
- Simple adjustment permits raising and lowering of the center foot which allows for sewing different thicknesses of material and thus assures positive stitching
- Standard attachments easily installed
- Compound feed, walking foot mechanism insures even feeding of material
- Locking stitch regulator prevents changes in stitch length from vibration
- All gear driven hook mechanism. Large horizontal axis hook.
- Safety clutch with push-button re-engagement. *No Safety Clutch on 206RBL-30-1*
- Long arm provides extra large work area
- Available with 18", 25" and 30" arms
- Factory built solid molded casting
- Built-in bobbin winder



Available Option:
Adjustable, spring-loaded, retractable,
SWING ARM GUIDE.



Special features for the 206RBL30-1

- Oil Pump System with Pump, Oil Pan and Adjustable Oil Flow
- Adjustable Oil Gauge
- Engageable Center Handwheel (*No Safety Clutch on 206RBL-30-1*)


SPECIFICATIONS

Speed, Max. (S.P.M.)	1800*
Clearance Under Foot	9/16" (14mm)
Needle Bar Stroke	1-5/16" (33 mm)
Stitch Length, Max.	2-1/2 s.p.i. (10 mm)
Needle	135 x 17
Bobbin	Metal 18034
	Pre-wound M
Hook	18033
Work Space 206RBL-25	25" (635 mm)
Bed Size 206RBL-25	7" x 33 ⁹ / ₁₆ " (178 x 852 mm)
Stitch Type	301

* Speed depends on thread, material and operation.



Optionally available from Clinton Industries:
Automatic Footlift and Automatic Backtack



FOOTLIFT



BACKTACK