

Since 1898
CONSEW®

Model CN2053R Series

CN2053R-1A

-1A

CN2053R-2A

-2A

CN2253R-1A Double Needle *Photo on next page*

WITH

HORIZONTAL AXIS ROTARY HOOK

REVERSE FEED

ADJUSTABLE REVERSE STITCH LENGTH

COMBINATION ZIG-ZAG AND STRAIGHT STITCHER

NEEDLE POSITION ADJUSTMENT (*Right • Center • Left*)

METAL GEARS (HARDENED STEEL)



SINGLE NEEDLE

DROP FEED

ZIG-ZAG

LOCKSTITCH MACHINE

Models CN2053R-1A / CN2053R-2A / CN2253R-1A

APPLICATIONS

- For sewing light to medium heavy weight fabrics including clothing, shoes and caps, leather articles, bags and more
- For attaching lace, elastic band, bottom hemming, edge stitching, butted seaming, applique and similar operations
- Federal stitch type 304
- CN2053R-2A has Stitch type 308 (*used to secure lines on parachutes*)
- CN2253R-1A for piping and cording. Top of material will show a double-needle 5 mm stitch, and bottom of material will show a zig-zag stitch



FEATURES


- Horizontal axis transverse rotary hook
- Dial stitch regulator
- Locking zig-zag width regulator lever
- Straight stitches when zig-zag set to "0" using straight stitch locking device
- Stitches per minute — up to 1800*
- Reverse stitching with adjustable stitch length
- Metal gears (hardened steel)
- Built-in free-hand monogramming lever



CN2253R-1A with Double Needle

SPECIFICATIONS

CN2053R-1A		CN2053R-2A	CN2253R-1A
Speed, Max. (S.P.M.) *	1800	(same specs as at left)	(same specs as at left)
Clearance Under Foot	by hand 15/64" (6 mm)	"	"
	by knee 25/64" (10 mm)	"	"
Needle Bar Stroke	1 6/25" (31.5 mm)	"	"
Stitch Length, Max.	5 s.p.i. (5 mm)	"	"
Needle	135 x 5	"	Staggered Double needle with a 5 mm needle spacing
Bed Size	7" x 15 11/16" (178 x 398.5 mm)	"	"
Work Space	8 5/16" (211 mm)	"	"
Stitch Width Max.	11/32" (9 mm)	"	"
Stitch Type	304 •••••	308 •••••	Top of material will show a double-needle 5 mm stitch and bottom of material will show a zig-zag stitch



Closeup of needle adjusted to left position.

* Speed depends on width of zig-zag, material and thread.