



# Model P1560RB-DD and -7DD series

Designed for automotive, marine, leather, canvas and general upholstery.

The Automatic Footlift and Reverse on these machines operates Pneumatically (Air) and require a compressed air source (not supplied by Consew.)

**Automatic Function Machines (-DD)** 

The (-DD) does NOT have the Automatic Thread Trim

P1560RB-14-DD/220 14"

P1560RBL-18-DD/220 18"

P1560RBL-25-DD/220 25"

Currently Available in 220V 1-phase Version ONLY.

**Full Automatic Function Machines (-7DD)** 


The (-7DD) has Automatic Thread Trim

P1560RB-14-7DD/220 14"

P1560RBL-18-7DD/220 18"

P1560RBL-25-7DD/220 25"

**Currently Available in 220V 1-phase Version ONLY.** 





P1560RB-14-DD/220 14" workspace

P1560RBL-18-DD/220 18"

25" P1560RBL-25-DD/220

Automatic Function Machines (-DD) No Auto Thread Trim Full Automatic Function Machines (-7DD) with Auto Thread Trim

P1560RB-14-7DD/220 14" workspace

P1560RBL-18-7DD/220 18"

P1560RBL-25-7DD/220 25"

Also Available P1565RB-series that has split needle bar.

## APPLICATIONS

- For sewing light to heavy-weight fabric, canvas, leather, vinyl, synthetics and various laminated and coated materials
- Designed for stitching such products as auto, boat and furniture upholstery, tarpaulins, covers, awnings, tents, umbrellas, handbags, luggage, travelware accessories, sports and camping equipment, wearing apparel, outdoor clothing, footwear, foundation garments, orthopedic appliances, etc.

## Features for -7DD

- Large Top Load Bobbins
- Built-in Bobbin Winder
- Walking Foot
- Climbing Device
- Roll-In, tucks the top thread under fabric when it starts
- Automatic Foot Lift
- Automatic Reverse
- Semi-Autopmatic Lubrication
- Convenient push-button control switches
- Automatic Thread Trim (on -7DD only)

## Features for -DD


Same as -7DD except it does NOT have the Automatic Thread Trim



Control **Panel** 

## P1560RB-14-7DD/220V

This is a fully automatic machine, and includes the air cylinders for the footlift, reverse feed, and trim functions.




TWO NEEDLE WALKING

Treadle control lever. This is plugged in to the motor's

electronics and is connected to the foot treadle with the treadle rods

## **THREAD TRIMMER ON -7DD**



Thread Trimmer Knife



Thread Trimmer Solenoid

## **SPECIFICATIONS**

## P1560RB series

Speed, Max. (S.P.M.)	* 2500 - 3000*
Clearance Under Foot	9/16" (14mm)
Presser Foot Lift By	Hand: (9 mm)
Ву	Knee: (16 mm)
Stitch Length, Max.	Max. 9mm adjustment by dial
Needle	135 x 17
Bobbin - Pre-wound	U or S
Work Space	14"(355 mm), 18"(457 mm)
	25"(635 mm)
Stitch Type	301
Needle Gauges 1/4" to 1" (Custom gauges also available)  Largest gauge for the -7DD machines is 1 inch	
* Speed depends on thread, material and operation.	

Currently Available in 220v 1-phase Version ONLY.